


Vertex Pole-Top Solar Lighting System

Stand-Alone LED Lighting System



Product Overview

Mission critical lighting for discerning organisations that value reliability & performance.

The Vertex® solar lighting system comprises the StreetLED luminaire mounted on a fixed solar pole with the solar panel array attached at the top.

The batteries, Charge controller and Vertex® EMS (energy management systems) are securely housed in the pole-top mounted housing behind a sturdy steel locked door.

Performance Summary

Designed and Assembled in Australia

Autonomy: Up to 5 Days

Lumen Output: Up to 3,500 Lumens

Colour Rendering Index: Minimum 70 CRI

Colour Temperature: 4000K

Warranty: 5 Year Limited Warranty with Performance Guarantee

Specification Criteria

Product	Arrangement	Power Setting	Optic	CCT	Height	Finish	Footing Type	Power Profile
Vertex® Pole-Top	Single	14W	Standard	40K	4m	Galvanised (HDG)	Pier Cage	Dusk-Dawn
		28W	Aeroscreen	30K	6m	Powder Coat	Slab Cage	4-Hour / Off
								4-Hour / Dim
								5 Hour / Off
								5 Hour / Dim
							Other / Custom	

Power profiles explained:

- Dusk -Dawn – Runs the luminaire at static power level from dusk through to dawn
- 4 Hour / Off – Runs luminaire from dusk for a total time of 4 hours and then completely switches off the luminaire
- 4 Hour / Dim – Runs luminaire from dusk for a total time of 4 hours and then dims the luminaire to a pre-set level for the rest of the night
- 5 Hour / Off – Runs luminaire from dusk for a total time of 5 hours and then completely switches off the luminaire
- 5 Hour / Dim – Runs luminaire from dusk for a total time of 5 hours and then dims the luminaire to a pre-set level for the rest of the night
- Other / Custom – Orca Solar can program systems for dimming level and or running time according to project requirements.

Vertex Pole-Top Solar Lighting System

Stand-Alone LED Lighting System

Standard Visor



Aeroscreen Visor



PRODUCT / PERFORMANCE SUMMARY

- High performance street luminaire
- Designed specifically to meet Australian/New Zealand road lighting standards
- The optics and LED light source are optimised to provide the maximum spacings complying with AS1158-3.1 Category P
- Available with self-cleaning Standard or Aeroscreen visor
- The self-cleaning visor minimises light loss due to dirt accumulation, resulting in a highly energy efficient and low maintenance luminaire
- Optical chamber sealed to IP66 ingress protection
- Minimum 70 CRI
- CCT 4000K (standard)

Mechanical Characteristics:

- Pressure die-cast aluminium body (marine grade)
- Weight: 6.1kg
- Self-cleaning acrylic visor (Standard visor)
- IP66 optical chamber
- Stainless 304 steel access clips
- Easy to replace visor hinged with quick access clips
- 27mm to 34mm Spigot Entry
- Hinged driver compartment cover with quick access clips

PRODUCT DESCRIPTION

Engineered and crafted in Australia, the StreetLED MKII is a high-performance luminaire designed specifically to meet Australian/New Zealand minor road lighting requirements.

The optical system with LED light source is optimised to provide the maximum spacing complying with AS1158-3.1 Category P.

The optical chamber sealed to IP66 ingress protection and the self-cleaning visor minimises light loss due to dirt accumulation, reducing maintenance and resulting in a highly energy efficient luminaire

Power Setting	4000K
	Initial Lumens*
14W	2,146 (Standard Visor)
14W	2,068 (Aeroscreen Visor)
28W	3,466 (Aeroscreen Visor)

* Estimated lumen output at designated power level de-rated from initial (28 Watt)

Optical Characteristics:

- CCT: Available in 4000K and 3000K
- CRI: > 70
- Optical chamber sealed to IP66

Environmental & Standards:

- Ambient Operation Temps: -10 to 40°C
- EMC compliant: AS/NZS CISPR15, AS/NZS 60598.1 & AS/NZS TS 1158.6: Luminaires - Performance

Vertex Pole-Top Solar Lighting System

Stand-Alone High Output LED Lighting System

Autonomy: Vertex® solar lighting systems are scaled to suit applications using NASA solar radiation data based on conditions recorded at location of installation.

Solar Panel: Photovoltaic panel(s) scaled sufficiently to match power load and Vertex® system requirements with 25 Year performance guarantee.

Panel systems are sized specific to location conditions and autonomy requirements

Batteries: Long life batteries VRLA Gel batteries with 5 Year + 5 Year

Pro-Rate warranty on SunGEL branded batteries

Battery systems are sized and quantified specific to location conditions and autonomy requirements in accordance with AS/NZS 4509 and AS/NZS 5139 (4086).

** 5 Year warranty applies to systems using SunGEL branded batteries only. Where systems are supplied with alternative battery options by other manufacturers, warranty periods may vary.*

Charge Controller: Advanced MPPT (maximum power point tracking) with short circuit and over current protection. Minimum efficiency of 99.5% and automatic limit function of maximum PV input power, ensuring no overload under any circumstance.

LED Driver: Wide input voltage and high precision constant current control with linear PWM duty cycle dimming control. Minimum 92% efficiency under -40-65° ambient conditions

LED Drive Controller: Four function drive control with pre-set dimming level and timeframe programming including autonomous power adjustment synced to battery voltage and ambient temperature conditions.

Solar Pole: Specifically designed for the Vertex® solar lighting systems, six metre fixed solar pole with battery box to securely house the Vertex® EMS and batteries behind a secure steel door and provide ventilation as per AS4509.

Batteries are securely placed on shelves above the Vertex® EMS which is fixed to a purpose-built mounting bracket positioned for easy access during installation and maintenance.

Compliance

Vertex® solar lighting systems provide a minimum of 30% solar panel oversupply co efficient as an extra reliability measure in accordance with AS4509.2 (Australian standards for standalone power systems),

HDG (Hot Dipped Galvanised) steel poles and cage footings designed in accordance with AS4100, AS3679, AS1163 and AS1154

The Vertex® Energy Management System houses the lighting controller, LED driver and safety switches, mounted on fire retardant board. Designed and assembled in Australia, conforming to AS 3000 electrical safety standards and AS 4509.2 standalone power systems

